sammic

VACUUM SEALER SE-208

Tabletop model. 8 m³/h. 280 mm





SALES DESCRIPTION

280 mm sealing bar.

8 m³/h Busch vacuum pump.

Vacuum controlled by sensor.

- √ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- ✓ Digital keyboard.
- Control panel equipped with display indicating the exact vacuum percentage.
- √ "Pause" button to marinate food.
- ✓ Safe liquid packing thanks to sensor control.
- ✓ Double seal.
- √ Cordless sealing bar.
- √ Bag-sealing programme.
- ✓ Pulse-controlled decompression.
- √ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of highly durable polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- √ NSF-listed model.

INCLUDES

- √ Sensor controls
- ✓ Up to 10 seconds of extra vacuum pull
- ✓ Soft air function
- ✓ Dry oil cycle
- √ BUSCH pump
- √ NSF approved
- √ Clear methacrylate lid
- √ Filling plate

OPTIONAL

- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and
- accessories
- Additional filling plates

SPECIFICATIONS

Pump capacity: 8 m³/h

Pump capacity (60 Hz): 10 m³/h

Bar length: 280 mm Total loading: 450 W

Vacuum pressure (maximum): 2 mbar

Plug: --

Internal dimensions

- √ Width: 288 mm
- ✓ Depth: 333 mm
- ✓ Height: 110 mm

External dimensions (WxDxH)

- √ Width: 337 mm
- ✓ Depth: 431 mm
- ✓ Height: 331 mm

Net weight: 32 Kg

Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

Crated dimensions

400 x 525 x 390 mm Gross weight: 35 Kg

AVAILABLE MODELS

1141080 SE-208 230/50-60/1

1141081 SE-208 120/50-60/1

1140633 SE-208 230/50-60/1 AUS


* Ask for special versions availability











phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty